

GoRugged R3000 Quad

Industrial Cellular VPN Router with 4 Ethernet Ports

For GPRS/EDGE/UMTS/HSPA+/4G LTE Networks

Robustel GoRugged R3000 Quad is a rugged cellular router offering state-of-the-art mobile connectivity for machine to machine (M2M) applications.

Key Features

- Dual SIM redundancy for continuous cellular connections supports 2G/3G/4G
- 4 Ethernet ports for layer 2 switch
- WAN link management: cellular WAN/Ethernet WAN/WLAN WAN backup
- VPN tunnel: IPSec/OpenVPN/PPTP/L2TP/GRE/DMVPN
- Supports GRE over IPSec/L2TP over IPSec
- Supports Modbus gateway (Modbus RTU/ASCII to Modbus TCP) and Modbus Master
- Supports GPS&GLONASS (optional), provides real time location and tracking
- Supports 802.11 b/g/n Wi-Fi (optional), AP and client mode
- Supports SDK, provides user programmatic interface
- Supports 802.1Q VLAN Trunk
- Supports PPPoE Bridge (IP Passthrough)
- Auto reboot via SMS/Caller ID/Timing
- Support alarm via Email, SMS, SNMP trap
- Support AAA and FTP
- Supports RobustLink (centralized M2M management platform, to remote monitor, configure and update firmware)
- Supports RobustVPN (Cloud VPN Portal, to provide easy and secure remote access for PLCs and machines)
- Flexible Management methods: Web/CLI/SNMP/RobustLink
- Firmware upgrade via Web/CLI/USB/SMS/RobustLink
- Various interfaces: RS-232/RS-485/Console/USB/Ethernet
- Wide range input voltages from 9 to 60 VDC and extreme operating temperature

Optional Accessories (can be purchased separately)

- AC/DC power supply adapter
- Rubber SMA antenna
- 35 mm DIN rail mounting kit or wall mounting kit
- Diversity antenna for HSPA+/LTE



Applications

- ATM/Vending Machine Connectivity
- Solar/Wind Energy Monitor
- Distribution Automation
- Automatic Meter Reading
- Industrial Automation
- IP Video Surveillance
- Remote Devices

Regulatory and Type Approvals

- Approval & Certificates: CE, R&TTE, RCM, RoHS, WEEE
- EMC:

EMI: EN 55022 (2006/A1: 2007) Class B

EMS: IEC 61000-4-2 (ESD) Level 3,
IEC 61000-4-3 (RS) Level 4
IEC 61000-4-4 (EFT) Level 4,
IEC 61000-4-5 (Surge) Level 4,
IEC 61000-4-6 (CS) Level 3,
IEC 61000-4-8 Level 4

Packing List

- Robustel R3000 Quad router
- Terminal block for power, and serial port
- Document and software CD

GoRugged R3000 Quad

Industrial Cellular VPN Router with 4 Ethernet Ports

Specifications

Cellular Interface

- Standards: GSM/GPRS/EDGE/UMTS/HSPA+/FDD LTE
- HSPA+: DL/UL 21/5.76 Mbps, fallback to 2G
- FDD LTE: DL/UL 100/50 Mbps, fallback to 3G/2G
- SIM: 2 x (3 V & 1.8 V)
- Antenna interface: SMA female

System

- LED indicators: RUN, PPP/WLAN, USR, RSSI, NET, SIM
- Built-in RTC, Watchdog, Timer
- Expansion: 1 x USB 2.0 host up to 480 Mbps
- Storage: 1 x Micro SD

WLAN Interface (Optional)

- Standards: 802.11b/g/n up to 65 Mbps, AP and Client mode
- Frequency band: 2.400 - 2.500 GHz (2.4 GHz ISM band)
- Security: Open, WPA, WPA2, WEP
- Encryption: AES, TKIP, WEP64, WEP128
- Antenna interface: RP-SMA female
- Transmission power: 802.11b: 17dBm, 802.11g/n: 15dBm
- Reception sensibility: 1M: -97dBm, 2M: -93dBm, 6M: -91dBm, 11M: -89dBm, 54M: -75dBm, 65M: -72dBm

Serial Interface

- Number of ports: 1 x RS-232 or 1 x RS-485
- ESD protection: ± 15 KV
- Parameters: 8E1, 8O1, 8N1, 8N2, 7E2, 7O2, 7N2, 7E1
- Baud rate: 300bps to 230400bps
- RS-232: TxD, RxD, RTS, CTS, GND
- RS-485: Data+ (A), Data- (B)
- Interface: 3.5 mm terminal block with lock

Ethernet Interface

- Number of ports: 4 x 10/100 Mbps, 4 LANs or 3 LAN + 1 WAN
- Magnet isolation protection: 1.5 KV

GPS & GLONASS Interface (Optional)

- Antenna interface: SMA female, with 50 ohms impedance
- Tracking sensitivity: GPS: better than -148 dBm
GLONASS: better than -140 dBm
- Horizontal position accuracy: GPS: 2.5 m
GLONASS: 4.0 m
- Protocol: NMEA-0183 V2.3

Software

- Network protocols: PPP, PPPoE, TCP, UDP, DHCP, ICMP, NAT, DMZ, RIP v1/v2, OSPF, DDNS, VRRP, HTTP, HTTPS, DNS, ARP, QoS, SNMP, Telnet, VLAN, SSH2, etc
- VPN tunnel: IPSec/OpenVPN/PPTP/L2TP/GRE/DMVPN
- Firewall: SPI, anti-DoS, Filter, Access Control
- Management: Web, CLI, SNMP v1/v2/v3, SMS, RobustLink
- Serial port: TCP client/server, UDP, Modbus RTU/ASCII to Modbus TCP, Virtual COM (COM port redirector)
- RobustLink: Centralized M2M management platform
- RobustVPN: Cloud VPN Portal

Power Supply and Consumption

- Power supply interface: 5 mm terminal block with lock
- Input voltage: 9 to 60 VDC
- Power consumption: Idle: 100 mA@12 V
Data link: 400 mA (peak) @12 V

Physical Characteristics

- Housing & weight: Metal, 500 g
- Dimension: 125 mm x 108 mm x 45 mm
- Installation: 35 mm DIN rail, wall mounting or desktop

Selection and Ordering Data

Model No.	Description	Operating Environment
R3000-Q3PA	HSPA+ Router, 4 Ethernet ports, 1 RS232 port, HSPA+ 850/900/1900/2100 MHz	-40 to 85°C/5 to 95% RH
R3000-Q3PB	HSPA+ Router, 4 Ethernet ports, 1 RS485 port, HSPA+ 850/900/1900/2100 MHz	-40 to 85°C/5 to 95% RH
R3000-Q4LA	FDD LTE Router, 4 Ethernet ports, 1 RS232 port, FDD LTE 800/900/1800/2100/2600 MHz	-40 to 85°C/5 to 95% RH
R3000-Q4LB	FDD LTE Router, 4 Ethernet ports, 1 RS485 port, FDD LTE 800/900/1800/2100/2600 MHz	-40 to 85°C/5 to 95% RH

Contact:

www.robustel.com
info@robustel.com